

ALIMAK SCANDO 650 FC /39

3.9 m car with two vertical doors	(C52)
3.9 m car with three vertical doors	(C53)
3.9 m car with one load ramp and one vertical door	(C55)
3.9 m car with one load ramp and two vertical doors	(C56)

CAPACITY		(C52)	(C53)	(C55)	(C56)
Payload capacity (fuse 63 A)	kg	1500	1400	1400	1300
(fuse 80 A)	kg	1700	1700	1600	1500
Speed 50 Hz / 60 Hz	m/min	0-54	0-54	0-54	0-54
Max. lifting height ¹	m	200	200	200	200
No. of buffer springs	pcs.	2	2	2	2
Safety device type GFD	P/N	9099255-8012			

1. Increased lifting height on request

CAR DIMENSIONS		INTERNAL	EXTERNAL
Width	mm	1500	
Length / (E)	mm	3900	4020
Height	mm	2300	
Sliding door opening, W × H	mm	1500 × 2200 or 3200 × 2000 ¹	

1. Width 3200 mm applies to cars with a third vertical door, (location C)

ELECTRICAL DATA ¹	
Power supply range	400-500 V, 50 or 60 Hz, 3 Phase
At 400 V / 50 Hz:	
Power supply fuses	A~ 63 or 80 alternatively
Dual motor machinery	kW 2 × 11
Starting current (fuse 63 A)	A~ 69
(fuse 80 A)	88
Power consumpt. (fuse 63 A)	kVA~ 42
(fuse 80 A)	53
Power cable guiding system	Cable basket (≤ 100 m)

1. Data for other voltages on request

TRANSPORT DIMENSIONS	
Base unit incl. ground enclosure	
Length (F)	mm 4520 ¹
Maximum height	mm 3100

1. Add additional 100 mm if accessories for pipe support equipment are added

ENCLOSURE WIDTH		SINGLE (G)	DUAL (H)
Standard doors	mm	2550	4280
Additional door (location C)	mm	2600	4380




Fig B57